



UNILIN Evola-Antivlam[®]

Melamine faced fire-retardant and non-structural chipboard for interior and furniture available in an extensive range of UNILIN Evola designs

Melamine faced fire-retardant and non-structural P2 chipboard. UNILIN Evola-Antivlam is suitable for dry conditions, service class 1, mainly used for interior and furniture. This fire-retardant product is B-s1,d0 certified. UNILIN Evola-Antivlam is made from 100% recovered wood.

Applications

- Interior design
- Furniture production
- Vertical applications

Characteristics



P2



Melamine faced chipboard



Fire retardant (B-s1,d0)



100% recovered wood



UNILIN Evola-Antivlam[®]

Applications

UNILIN Evola-Antivlam is applied in different applications for interior and furniture design mainly where extra fire regulations are required.

Advantages

- In perfect colour match with HPL & edging tape for all UNILIN Evola stockrange decors
- Fire retardant
- Easy to clean
- Resistant to UV light
- Budget friendly
- Easy to process
- 100% recovered wood

Technical specifications

Performance characteristics	Unit	Ranges of nominal thickness (mm)		
		>10-13	>13-20	>20-25
Bending strength EN 310	N/mm ²	11	11	10,5
Bending stiffness EN 310	N/mm ²	NPD	NPD	NPD
Internal bond EN 319	N/mm ²	0,40	0,35	0,30
Water vapour permeability	Wet %	16	15	15
	Dry %	50	50	50

Finish

This melamine faced board is possible to have in combination with a wide variety of designs.

The wood decors not only look incredibly lifelike, also the structures feel particularly authentic. Combined with plain colours, basis on international trends, the designs deliver unprecedented freedom in creativity for interior projects.

Available dimensions / thicknesses

All designs in the UNILIN Decorative range are available in combination with UNILIN Evola-Antivlam board.

The standard size is 2800 x 2070.

Thicknesses 10 and 19 mm are part of the fast lane service range and can be collected within ten or fifteen working days, starting from a volume of two units.

Certificates

UNILIN Division Panels is actively committed to sustainable forest management. UNILIN Evola-Antivlam is available on demand in PEFC and/or FSC labelling.